NSN 5307-01-350-2633

Locked In Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-01-350-2633

| view Offiline at https://aerobasegroup.com/nsi//0007-01-000-2000 |
|--|
| Thread Class: |
| 3a nut thread2a stud thread |
| Thread Direction: |
| Right-hand nut threadright-hand stud thread |
| Thread Length: |
| 0.380 inches nut thread and 0.440 inches nut thread0.297 inches stud thread and 0.327 inches stud thread |
| Locking Feature: |
| Ring, lock keyed |
| Overall Length: |
| Between 1.407 inches and 1.467 inches |
| End Application: |
| Pacer dawn |
| Thready Qty Per Inch (tpi): |
| 32 nut thread18 stud thread |
| Thread Size: |
| 0.190 inches nut thread0.312 inches stud thread |
| Distance From End Of Stud End Threads To Nut End: |
| Between 1.095 inches and 1.155 inches |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5734 a-286 cres assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Style Designator: |
| Locked in |
| Thread Series Designator: |
| Unjf nut threadunc stud thread |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A051a0 |
| |