NSN 5307-01-357-4496

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-357-4496

| Thread Class: |
|--|
| 2a nut thread2a stud thread |
| Thread Direction: |
| Right-hand nut threadright-hand stud thread |
| Thread Length: |
| 1.220 inches nut thread0.730 inches stud thread |
| Shoulder Diameter: |
| 0.750 inches |
| Shoulder Length: |
| Between 3.248 inches and 3.252 inches |
| Overall Length: |
| 6.000 inches |
| Nut End Shank Length: |
| 0.340 inches |
| Distance Across Flats: |
| 0.620 inches |
| Thready Qty Per Inch (tpi): |
| 20 nut thread20 stud thread |
| Thread Size: |
| 0.500 inches nut thread0.500 inches stud thread |
| Stud End Shank Length: |
| 0.340 inches |
| Stud End Shank Diameter: |
| Between 0.558 inches and 0.559 inches |
| Nut End Shank Diameter: |
| Between 0.558 inches and 0.559 inches |
| Material: |
| Copper alloy 715 |
| Material Specification: |
| Mil-c-15726, soft temper military specification single material response |
| Style Designator: |
| Shouldered |
| Thread Series Designator: |
| Unf nut threadunf stud thread |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| _ |
| Demilitarization: |
| No |
| Fiig: |

A051a0

NSN 5307-01-357-4496

Shouldered Stud - Page 2 of 2



Mil-std (military Standard):

Mil-c-15726 spec.