NSN 5307-01-357-4498 Shouldered Stud - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5307-01-357-4498 |
|--|
| Thread Class: |
| 2a nut thread2a stud thread |
| Thread Direction: |
| Right-hand nut threadright-hand stud thread |
| Thread Length: |
| 0.950 inches nut thread0.940 inches stud thread |
| Shoulder Diameter: |
| 0.880 inches |
| Shoulder Length: |
| Between 3.248 inches and 3.252 inches |
| Overall Length: |
| 6.440 inches |
| Nut End Shank Length: |
| 0.340 inches |
| Distance Across Flats: |
| 0.750 inches |
| Thready Qty Per Inch (tpi): |
| 18 nut thread18 stud thread |
| Thread Size: |
| 0.625 inches nut thread0.625 inches stud thread |
| Stud End Shank Length: |
| 0.840 inches |
| Stud End Shank Diameter: |
| Between 0.624 inches and 0.625 inches |
| Nut End Shank Diameter: |
| Between 0.624 inches and 0.625 inches |
| Special Features: |
| Flat sides of shoulder are 0.500 in. Long, 0.250 in. From nut end shank; 0.560 in. Dia. Groove, 0.060 in. Wide between shank and threads |
| on stud and nut ends |
| Material: |
| Nickel alloy k-500 |
| Material Specification: |
| Qq-n-286 form 2, annealed federal specification single material response |
| Style Designator: |
| Shouldered |
| Thread Series Designator: |
| Unf nut threadunf stud thread |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5307-01-357-4498 Shouldered Stud - Page 2 of 2



Fiig:

A051a0