## NSN 5307-01-383-5972

Plain Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-383-5972

## Thread Class:

3a nut thread

Thread Pitch Diameters:

+0.2338/+0.2343 inches stud thread

## **Thread Direction:**

Right-hand stud thread

#### **Thread Length:**

0.600 inches stud thread

#### **Overall Length:**

1.062 inches

## Distance From Cotter Pin Hole Centerline To Nut End:

0.110 inches first hole

**Cotter Pin Hole Diameter:** 

0.065 inches first hole and 0.072 inches first hole

## Thready Qty Per Inch (tpi):

28 nut thread

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Thread Size:

0.250 inches stud thread

Criticality Code Justification:

Thsd

Surface Finish:

63.0 microinches shank

## **Special Features:**

Stud thread is safety critical; unified form special per fed-std-h28/2. Apply one coat of mil-p-23377, type 1, cl 1 or 3 and two top coats of mil-c-46168, color code 33538 per fed-std-595 to top of nut end

Material:

Steel comp 8740

## **Material Specification:**

Ams 6322 assn standard single material response

#### Surface Treatment:

Cadmium

#### **Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

#### **Thread Series Designator:**

Uns stud thread

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5307-01-383-5972

Plain Stud - Page 2 of 2

Fiig: A051a0

