NSN 5307-01-398-0335

Locked In Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-398-0335

| Thread Class: |
|--|
| 3a nut thread b |
| Thread Direction: |
| Right-hand nut thread b |
| Thread Length: |
| 0.673 inches nut thread a and 0.703 inches nut thread a |
| Locking Feature: |
| Ring, lock serrated |
| Overall Length: |
| 1.868 inches |
| Distance From Serrated Portion To Nut End: |
| Between 0.985 inches and 1.015 inches |
| Distance From Serrated Portion To Stud End: |
| Between 0.848 inches and 0.888 inches |
| Distance From Serrated Portion To End Of Stud Thread: |
| Between 0.151 inches and 0.191 inches |
| Serration Quantity: |
| 20 |
| Thready Qty Per Inch (tpi): |
| 24 nut thread a |
| Hardness Rating: |
| 277.0 brinell hultgren |
| Thread Size: |
| 0.437 inches nut thread b |
| Surface Finish: |
| 63.0 microinches shank |
| Serration Included Angle: |
| 102.0 degrees |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5731 assn standard single material response or ams5734 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Style Designator: |
| Locked in |
| Thread Series Designator: |
| Unjf nut thread b |
| Shelf Life: |

N/a

NSN 5307-01-398-0335

Locked In Stud - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A051a0