## NSN 5307-01-528-5500

Recessed Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-01-528-5500

Length Of Recessed Portion Of Shank:  0.125 inches  Diameter Of Recessed Portion Of Shank:  0.347 inches  End Application:  Mv-22 aircraft (v-22 Irip 1 e-nsn isil)  Product Name:  Inavy: stud, straight  Special Features:  Threads are 0.375-24unjf-3a per mil-s-8879 and 0.375-16njs per mil-s-8879  Material:  Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification:  Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment:  Cadmium  Surface Treatment Specification:	
Diameter Of Recessed Portion Of Shank: 0.347 inches  End Application:  Mv-22 aircraft (v-22 Irip 1 e-nsn isil)  Product Name: Inavy: stud, straight  Special Features:  Threads are 0.375-24unjf-3a per mil-s-8879 and 0.375-16njs per mil-s-8879  Material: Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification:  Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment:  Cadmium	
Diameter Of Recessed Portion Of Shank:  0.347 inches  End Application:  Mv-22 aircraft (v-22 Irip 1 e-nsn isil)  Product Name:  Inavy: stud, straight  Special Features:  Threads are 0.375-24unjf-3a per mil-s-8879 and 0.375-16njs per mil-s-8879  Material:  Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification:  Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment:  Cadmium	
End Application:  Mv-22 aircraft (v-22 Irip 1 e-nsn isil)  Product Name: Inavy: stud, straight  Special Features: Threads are 0.375-24unjf-3a per mil-s-8879 and 0.375-16njs per mil-s-8879  Material: Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification: Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment: Cadmium	
End Application:  Mv-22 aircraft (v-22 Irip 1 e-nsn isil)  Product Name:  Inavy: stud, straight  Special Features:  Threads are 0.375-24unjf-3a per mil-s-8879 and 0.375-16njs per mil-s-8879  Material:  Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification:  Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment:  Cadmium	
Mv-22 aircraft (v-22 Irip 1 e-nsn isil)  Product Name: Inavy: stud, straight  Special Features: Threads are 0.375-24unjf-3a per mil-s-8879 and 0.375-16njs per mil-s-8879  Material: Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification: Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment: Cadmium	
Product Name: Inavy: stud, straight  Special Features: Threads are 0.375-24unjf-3a per mil-s-8879 and 0.375-16njs per mil-s-8879  Material: Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification: Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment: Cadmium	
Inavy: stud, straight  Special Features: Threads are 0.375-24unjf-3a per mil-s-8879 and 0.375-16njs per mil-s-8879  Material: Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification: Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment: Cadmium	
Special Features: Threads are 0.375-24unjf-3a per mil-s-8879 and 0.375-16njs per mil-s-8879  Material: Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification: Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment: Cadmium	
Threads are 0.375-24unjf-3a per mil-s-8879 and 0.375-16njs per mil-s-8879  Material:  Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification:  Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment:  Cadmium	
Material: Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification: Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment: Cadmium	
Steel comp 4140 or steel comp 4340 or steel comp 8740  Material Specification:  Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment:  Cadmium	
Material Specification:  Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment:  Cadmium	
Ams 6382 assn standard 1st material response or mil-s-5626 military specification 2nd material response or ams 6415 assn stan material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment:  Cadmium	
material response or mil-s-5000 military specification 4th material response or ams 6322 assn standard 5th material response or military specification all material responses  Surface Treatment:  Cadmium	
military specification all material responses  Surface Treatment:  Cadmium	dard 3rd
Surface Treatment: Cadmium	mil-s-6049
Cadmium	
Surface Treatment Specification:	
Qq-p-416, type 2, class 2 assn standard single treatment response	
Style Designator:	
Recessed	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A051a0	
Mil-std (military Standard):	
Mil-s-5626 spec.	