NSN 5307-01-644-2341

Shouldered Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-01-644-2341
Thread Class:
3a stud thread
Thread Direction:
Right-hand stud thread
Thread Length:
0.063 inches nut thread a
Shoulder Diameter:
Between 0.370 inches and 0.390 inches
Shoulder Length:
Between 0.064 inches and 0.074 inches
Overall Length:
1.026 inches
Nut End Shank Length:
0.325 inches
End Application:
Fighter aircraft (f18 e/f)
Thready Qty Per Inch (tpi):
32 stud thread
Thread Size:
0.182 inches stud thread
Stud End Shank Length:
0.325 inches
Stud End Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Nut End Shank Diameter:
Between 0.2172 inches and 0.2182 inches
Product Name:
Threaded stud pin, protuding head, titanium alloy
Special Features:
Finish: cetyl alcohol lube per hi-shear specification 305; threads modified - rolled per mil-s-8879; has internal hex drive, 0.0791-0.0806
across flats x 0.080-0.100 in. Deep; external threads on drive end are 0.250 in long; external threads on other end are 0.063 in. Long; hea
160, 000 psi tensile; double shear: 6, 130 pounds; tension: 3, 160 pounds
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 or ams4967 assn standard single material response
Surface Treatment:
Lubricant
Style Designator:
Shouldered
Thread Series Designator:
Unif stud thread

N/a

Shelf Life:

NSN 5307-01-644-2341

Shouldered Stud - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A051a0