

View Online at <https://aerobasegroup.com/nsn/5310-00-004-5033>

Hole Diameter:

Between 0.382 inches and 0.393 inches

Outside Diameter:

0.683 inches

Material Thickness:

Between 0.094 inches and 0.104 inches

End Application:

Mrap buffalo mk2a2; mrap - m-atv with cs13 pop and sne; mrap - cougar cat1 a2; medium mine protected vehicle - mmpv

Hardness Rating:

Between 45.0 rockwell c and 53.0 rockwell c

Special Features:

Certified free from mercury contamination

Material:

Steel comp 1060 or steel comp 1070 or steel comp 1078 or steel comp 1080

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate or zinc and chromate

Special Test Features:

Special quality control testing

Surface Treatment Specification:

Q-p-416, type2, class3 federal specification 1st treatment response or qq-z-325, type2, class2 federal specification 2nd treatment response

Style Designator:

Split helical-right hand

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

2 style and a class

Departure From Cited Document:

Material must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0