

View Online at <https://aerobasegroup.com/nsn/5310-00-004-5033>

**Hole Diameter:**

Between 0.382 inches and 0.393 inches

**Outside Diameter:**

0.683 inches

**Material Thickness:**

Between 0.094 inches and 0.104 inches

**End Application:**

Mrap buffalo mk2a2; mrap - m-atv with cs13 pop and sne; mrap - cougar cat1 a2; medium mine protected vehicle - mmpv

**Hardness Rating:**

Between 45.0 rockwell c and 53.0 rockwell c

**Special Features:**

Certified free from mercury contamination

**Material:**

Steel comp 1060 or steel comp 1070 or steel comp 1078 or steel comp 1080

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Cadmium and chromate or zinc and chromate

**Special Test Features:**

Special quality control testing

**Surface Treatment Specification:**

Q-p-416, type2, class3 federal specification 1st treatment response or qq-z-325, type2, class2 federal specification 2nd treatment response

**Style Designator:**

Split helical-right hand

**Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Or Standard:**

2 style and a class

**Departure From Cited Document:**

Material must conform to ships parts control center special quality control provisions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A022b0