NSN 5310-00-004-5119

Assembled Washer Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-004-5119 **Thread Class: Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Washer Outside Diameter:** Between 0.895 inches and 0.925 inches **Counterbore Diameter:** 0.604 inches nut and 0.614 inches nut **Overall Height:** Between 0.536 inches and 0.576 inches **Nut Style:** Flat with turned back edge **Nut Counterbore Depth:** 0.281 inches nut and 0.301 inches nut Width Across Flats: Between 0.741 inches and 0.752 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unjf Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Bearing Surface Finish:** 125.0 microinches Material: Steel comp 1137 nut or steel comp 11137 nut or steel comp 8740 nut **Material Specification:** Qq-a-225/6, t4 federal specification 1st material response washer or qq-a-250/13, t6 federal specification 2nd material response washer **Surface Treatment:** Cadmium nut and chromate nut **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response nut Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5310-00-004-5119

Assembled Washer Self-locking Nut - Page 2 of 2



Fiig:

A021a0

Mil-std (military Standard):

Mil-c-5541 spec.