NSN 5310-00-004-7355

Spline Plain Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-004-7355

| Thread Class: |
|--|
| 2b |
| Thread Direction: |
| Right-hand |
| Pilot Diameter: |
| Between 0.226 inches and 0.230 inches |
| Pilot Length: |
| Between 0.075 inches and 0.085 inches |
| Counterbore Diameter: |
| 0.187 inches first end and 0.190 inches first end |
| Nut Style: |
| Spline |
| Nut Diameter: |
| Between 0.309 inches and 0.315 inches |
| Nut Height: |
| Between 0.296 inches and 0.328 inches |
| Nut Counterbore Depth: |
| 0.198 inches first end and 0.213 inches first end |
| Thread Series: |
| Unc |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.164 inches |
| Countersink Angle: |
| 45.0 degrees second end |
| Material: |
| Steel comp 302 or steel comp 303 |
| Material Specification: |
| Qq-s-763, cond a federal specification 1st material response or astm a582 assn standard 1st material response or astm a276-55 assn |
| standard 2nd material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A021a0