Hexagon Self-locking Nut - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5310-00-018-7469

Inread Utass: By Thread Direction: Right-hand Locking Feature: Prevailing torque with nonmetallic insert Lubrication: Soluble lubricant Nut Style: Hexagon Nut Height: O.422 inches With Across Flats: Between 1.052 inches and 1.064 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unjf Thread Series: Unjf Thread Series: O.750 inches Contersink Angle: 250.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 incoinches Material: Plastic polyamide locking insert Surface Treatment Specification all treatment responses except insert Surface Treatment Specification all treatment responses except insert Chamfered or Washer faced Bearing Surface Type: Chamfered Type: Chamfered Type: Chamfered Direction: Naterial: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification Carje-16, type 2, cl 2 federal specification all treatment responses except insert Surface Treatment Specification Carje-16, type 2, cl 2 federal specification all treatment responses except insert Surface Treatment Specification Carje-16, type 2, cl 2 federal specification all treatment responses except insert Surface Treatment Specification Fig: Augusta Direction: Na Merici Measure: Fig: Augusta Direction: Augusta	Thread Classe	
Tread Direction: Right-hand Locking Feature: Prevailing torque with nonmetallic inset Lubrication: Soluble lubricant Nut Style: Hexagon Nut Height: 0.422 Inches With Across Flats: 28000 digrees fahrenheit Thread Streis: 2001 digrees fahrenheit Thread Streis: 2017 Thread Streis: 2030 digrees fahrenheit Thread Streis: 2030 digrees fahrenheit Thread Streis: 2047 2050 digrees fahrenheit Thread Streis: 2047 2050 digrees fahrenheit 2050 digrees nut Bearing Surface Truise: 2050 digrees nut Bearing Surface Finise: 2050 microinches Material: Platte polyamide locking insert Surface Treatment: 2040:prest nut Specification all treatment responses except insert Surface Treatment: Qu-p-416, type 2, cl 2 federal specification all treatment responses except insert Surface Treatment: <th>Thread Class:</th> <th></th>	Thread Class:	
Right-hand Locking Feature: Prevailing tarque with nonmetallic insert Lubrication: Soluble lubricant Nut Style: Hexagon Nut Height: 0.422 linches With Across Flats: Between 1.052 linches and 1.064 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unff Thread Streis: 260.0 degrees fahrenheit Thread Streis: 20.1 degrees fahrenheit Preversive: 20.50 degrees nut Betring Surface Type: 21.60 Solubrees nut Bearing Surface Type: 22.50 microinches Bearing Surface Type: 23.50 microinches Surface Treement: 24.50 microinches Surface Treement: 25.0 microinches Bearing Surface Type: 25.0 microinches Surface Treement: 25.0 microinches Cademium except insert and chromate except insert Surface Treement: Quep-416,		
Locking Feature: Prevailing torque with nonmetallic insert Lubrication: Soluble lubricant Nut Style: Hexagon Nut Height: 0.422 inches Witth Across Flats: Between 1.052 inches and 1.064 inches Tempature Rating: 250.0 degrees fahrenheit Thread Series: Unjf Thread Series: Oxfor Inches Parison (tpt): 16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 nicroinches Mariei: Plastia polyamide locking insert Surface Treatment Cadmium except insert and chromate except insert ment responses except insert Surface Treatment Specification: Na Na Daillatrization:: Na Thread Size: Daillatrization:: Na Daillatrization: <td></td> <td></td>		
Prevailing torque with nonmetallic insert Lubrication: Soluble lubricant Soluble lubricant Soluble lubricant Nut Style: Hexagon Nut Height: Aux Height: Aux Height: Aux Height: Aux Height: Aux Height: Between 1.052 inches and 1.064 inches Fureque Starten Externed Startes: Botween 1.052 inches and 1.064 inches Fureque Starten Externed Startes: Dot degrees fahrenheit Thread Startes: Dot degrees fahrenheit Thread Startes: Dot degrees fahrenheit Startead Startes: Dot degrees fahrenheit Startead Startes: Dot degrees nut Betaring Surface Type: Chamfered or washer faced Bearing Surface Finish: Data Startes: Data Starte	-	
Lubrication: Soluble lubricant Nut Style: Hexagon Nut Height: O 422 inches Width Across Flats: Between 1.052 inches and 1.064 inches Tempurature Rating: Estween 1.052 inches and 1.064 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unjf Thread Series: Unjf Thread Series: Orfo inches Contersink Angle: 88.0 degrees nut Bearing Surface Type: Contersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Tinish: 125.0 incroinches Materiat: Plastic polyamide locking insert Surface Treatment Cadmium except insert and chromate except insert Surface Treatment Specification app-416, type 2, cl 2 federal specification all treatment responses except insert Sheft Itie: Na Fig:		
Soluble lubricant Nut Style: Hexagon Nut Height: 0.422 inches Width Across Flats: Between 1.052 inches and 1.064 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Sories: Uniff Thread Sories: Uniff Thread Sories: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment Cadmium except insert and chromate except insert Surface Treatment Second Sociel Soc		
Nu Siyis Hexagon Nut Height: 0.422 inches Width Across Flats: Between 1.052 inches and 1.064 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unjf Thread Series: Unjf Thready Oty Per Inch (tpi): 16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification: Na Material: Plastic polyamide locking insert Surface Treatment Specification all treatment responses except insert Sheff Life: Na Material: Plastic Jone Surface Time Specification all treatment responses except insert Sheff Life: Na Material: Na Material: Plastic Jone Surface Theoret Specification all treatment responses except insert Sheff Life: Na Material: Plastic Jone Specification: Na Material: Plastic Jone Specification: Plastic Jone Specification:		
Hexagon Nut Height: 0.422 inches Witch Across Flats: Between 1.052 inches and 1.064 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unjf Thread Solution (npl): 16 Thread Size: 0.750 inches Contersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Platic polyamide locking insert Surface Treatment: Qu-p-161, type 2, d 2 federal specification all treatment responses except insert Shef Life: Na Lift Of Measure: ra Finalitarization: Na Surface Time: Na Diried Timest Specification all treatment responses except insert Surface Treatment: Na Surface Treatment Specification all treatment responses except insert Surface Treatment Specification all treatment responses except insert Surface Treatme		
Nut Height: 0.422 inches Width Across Flats: Between 1.052 inches and 1.064 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpl): 16 Thready Star 0.750 inches Coutersink Angle: 0.750 inches Baing Surface Type: Chamfered or washer faced Bearing Surface Type: 125.0 microinches Metrial: Plastic polyamide locking insert Surface Treatment: Quep-416, type 2, d12 federal specification all treatment responses except insert Shelf Life: Na Lift Of Measure: Image: Fig:		
0.422 inches Width Across Flats: Between 1.052 inches and 1.064 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unjf Thread Series: Unjf Thready Qty Per Inch (tpi): 16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches MateriaI: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification all treatment responses except insert Surface Timent Specification Angle Series Na Chamfered or Series Countersint Angle: Cadmium except insert and chromate except insert Surface Treatment Cadmium except insert and chromate except insert Surface Treatment Specification all treatment responses except insert Surface Treatment Cadmium except insert and chromate except insert Surface Treatment Specification all treatment responses except insert Na		
Width Across Flats: Between 1.052 inchess and 1.064 inches Tempurature Rating: 25.0.0 degrees fahrenheit Thread Series: Unif Thready Cdy Per Inch (tpi): 16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert cesponses except insert Surface Treatment Specification Qrap-416, type 2, cl 2 federal specification all treatment responses except insert Surface Treatment Specification Va Platic Measure: · Point of Measure: · Pointilatrization: · Pointilatrization: Pointilatrization: Pointilatrization:		
Between 1.052 inches and 1.064 inches Fempurature Rating: 25.0.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification Qr-p-416, type 2, cl 2 federal specification all treatment responses except insert Surface Treatment Specification Ivia Platic Measure: Ivia Ivia Platic Measure: Ivia Platic Measure: Ivia Ivia <t< td=""><td></td><td></td></t<>		
Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification all treatment responses except insert Sheff Life: N/a Plant of Measure: Int Of Measure: Image: No Fig:		
250.0 degrees fahrenheit Thread Series: Unif Thready Oty Per Inch (tpi): 16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment: Qup-416, type 2, of 2 federal specification all treatment responses except insert Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:		
Thread Series: Unif Thready Qty Per Inch (tpi): 16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification Qup-416, type 2, ol 2 federal specification all treatment responses except insert Sheff Life: N/a Entitle Measure: Image: No Fig:		
Hirif Thready Qty Per Inch (tpi): 16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification: Qr.p-416, type 2, of 2 federal specification all treatment responses except insert Shel Life: Na Plant of Measure: Image: Fig:		
Thready Qty Per Inch (tpi): 16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification: Qap-416, type 2, ol 2 federal specification all treatment responses except insert Shell Life: N/a Demilitarization: Image: Fig:		
16 Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Gurp-416, type 2, cl 2 federal specification all treatment responses except insert Surface Treatment: N/a Init of Measure: N/a Fine: Na Fine: Na Fine: No Fine: No Fine:		
Thread Size: 0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification Q-p-416, type 2, cl 2 federal specification all treatment responses except insert Surface Treatment: N/a Dit Of Measure: - - Demilitarization: No		
0.750 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification: Qr.p-416, type 2, cl 2 federal specification all treatment responses except insert Sufface Treatment Specification: Na Material: Na Dint Of Measure: Sufface Treatment: Demilitarization: No		
Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification Qq-p-416, type 2, cl 2 federal specification all treatment responses except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification: Qq-p-416, type 2, ol 2 federal specification all treatment responses except insert Shelf Life: N/a Unit Of Measure: - Demilitarization: No		
Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification Qq-p-416, type 2, d 2 federal specification all treatment responses except insert Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Countersink Angle:	
Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification all treatment responses except insert Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	88.0 degrees nut	
Bearing Surface Finish: 125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification all treatment responses except insert Shelf Life: N/a Dunit Of Measure: - Image: No Fig:	Bearing Surface Type:	
125.0 microinches Material: Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Cadmium except insert and chromate except insert Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification all treatment responses except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Chamfered or washer faced	
Material:Plastic polyamide locking insertSurface Treatment:Cadmium except insert and chromate except insertSurface Treatment Specification:Qq-p-416, type 2, cl 2 federal specification all treatment responses except insertShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Bearing Surface Finish:	
Plastic polyamide locking insert Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification all treatment responses except insert Shelf Life: N/a N/a Unit Of Measure: Demilitarization: No Fig:	125.0 microinches	
Surface Treatment: Cadmium except insert and chromate except insert Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification all treatment responses except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No	Material:	
Cadmium except insert and chromate except insert Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification all treatment responses except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:		
Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification all treatment responses except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:	
Qq-p-416, type 2, cl 2 federal specification all treatment responses except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium except insert and chromate except insert	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment Specification:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Qq-p-416, type 2, cl 2 federal specification all treatment responses except insert	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A021a0	Fiig:	
	A021a0	