

View Online at <https://aerobasegroup.com/nsn/5310-00-025-7010>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Lubrication:**

Dry film lubricant

**Nut Style:**

Hexagon

**Nut Height:**

0.407 inches

**Width Across Flats:**

Between 0.928 inches and 0.940 inches

**Tempurature Rating:**

450.0 degrees fahrenheit

**Thread Series:**

Unjf

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

0.625 inches

**Bearing Surface Type:**

Washer faced or chamfered

**Material:**

Steel comp 8740 or steel comp 4340 or steel comp 4140 or steel comp 4130

**Material Specification:**

Mil-s-6049 military specification 1st material response or ams 6322 assn standard 1st material response or mil-s-5000 military specification 2nd material response or ams 6378 assn standard 3rd material response or mil-s-18729 military specification 4th material response or ams 6350 assn standard 4th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-s-6049 spec.