NSN 5310-00-032-9682

Round Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-032-9682

| View Online at https://aerobasegroup.com/nsn/5310-00-032-9682 |
|---|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Drive Point Depth: |
| Between 0.105 inches and 0.115 inches |
| Nut Style: |
| Round |
| Nut Diameter: |
| Between 1.865 inches and 1.885 inches |
| Nut Thickness: |
| Between 0.490 inches and 0.510 inches |
| Drive Point Width: |
| 0.364 mils and 0.385 centimeters |
| Drive Point Quantity: |
| 6 |
| Drilled Hole Diameter: |
| 0.104 inches |
| Hole Type And Quantity: |
| 6 drilled |
| Thread Series: |
| Unef |
| Thready Qty Per Inch (tpi): |
| 18 |
| Hardness Rating: |
| Between 26.0 rockwell c and 32.0 rockwell c |
| Thread Size: |
| 1.125 inches |
| Hole Configuration Style: |
| Configuration f |
| Countersink Angle: |
| 119.0 degrees nut and 121.0 degrees nut |
| Material: |
| Steel comp 8735 or steel comp 8740 |
| Material Specification: |
| Ams 6320 assn standard 1st material response or ams 6282 assn standard 1st material response or ams 6322 assn standard 2nd material |
| response or ams 6323 assn standard 2nd material response or ams 6324 assn standard 2nd material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams 2400 assn standard single treatment response |
| Shelf Life: |

N/a

NSN 5310-00-032-9682

Round Plain Nut - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A021a0