NSN 5310-00-046-7486

Blind Rivet Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-046-7486

Inread Class: 3b Thread Direction: Right-hand Head Style: Flat Head Style: Flat Head Style: Flat Head Normeter: Between 0.766 inches and 0.796 inches Head Height: 0.088 inches Nut Style: Blind rivet wismooth round shank Nut Diameter: Between 0.486 inches and 0.490 inches Nut Length: Between 0.486 inches and 0.490 inches Nut Length: Between 0.486 inches and 0.490 inches Nut Length: Between 0.486 inches and 0.490 inches Undet To Decode: Unfor Thread Steles Unfor T	
Freed Direction:Right-handHead Style:FlatHead Diameter:Between 0.766 inches and 0.796 inchesHead Height:0.088 inchesNut Style:Bilnd rivet w/smooth round shankNut Diameter:Between 0.486 inches and 0.490 inchesNut Diameter:Between 0.486 inches and 0.490 inchesNut Diameter:Between 1.360 inches and 0.490 inchesValor Decode:40.115 to 0.200 inchesBread Stries:ClosedThread Stries:24Thread Stries:0.375 inchesMaterial:24ClosedMaterial:Stain stand and stand response or mil-s-6049 military specification 2nd material responseSurface TreatmentCadmimAuge-141, type 2, cl 3 federal specification single treatment responseSurface Treatment Specification:NaSurface Treatment Specification:NaSurface Treatment Specification single treatment responseSurface Treatment Specification:NaSurface Treatment Specification:Na<	Thread Class:
Right-hand Head Style: Flat Head Diameter: Between 0.766 inches and 0.796 inches Head Height: 0.088 inches Nut Style: Biln drivet wismooth round shank Nut Diameter: Between 0.486 inches and 0.490 inches Nut Leight: Between 1.360 inches and 1.390 inches Nut Leight: Between 1.360 inches and 1.390 inches Virale To Decode: +0.115 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thread Series: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmim Surface Treatment Specification: Aug-p-416, type 2, ol 3 federal specification single treatment response Shelf Life: Na Lifor Measure: Total Specification: Surface Treatment Specification:	
Head Style: Flat Head Diameter: Between 0.766 inches and 0.796 inches Head Height: 0.088 inches Nut Style: Bilnd rivet wismooth round shank Nut Diameter: Between 0.466 inches and 0.490 inches Nut Length: Between 1.360 inches and 1.390 inches Unable To Decode: +0.115 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thread Style: 0.375 inches Material: Stel comp 4037 or stel comp 8740 Material: Stel comp 4037 or stel comp 8740 Material Specification: Aisi ass standard 1st material response or mil-s-6049 military specification 2nd material response Strikee Treatment: Cadmium Surface Treatment Specification: Aug-p-416, type 2, d 3 federal specification single treatment response Shaft Life: Na Lift Of Measure: I Compliatization: I Thread Style: <t< td=""><td></td></t<>	
Flat Head Diameter: Between 0.766 inches and 0.796 inches HeidHeight: 0.088 inches Nut Style: Bind rivet wismooth round shank Nut Diameter: Between 0.466 inches and 0.490 inches Nut Length: Between 1.360 inches and 0.490 inches Unable To Decode: 4.015 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thread Series: 0.375 inches Material Stel comp 4037 or steel comp 8740 Material Specification: Striace Treatment: Cadmium Surface Treatment Specification single treatment response Cadmium Cadmium Surface Treatment Specification: Cadmium Cadmium Cadmium Surface Treatment Specification single treatment response Na Cadmium Cadmium Surface Treatment Specification single treatment response Surface Treatment Specification single treatment response N	-
Head Diameter: Between 0.766 inches and 0.796 inches Head Height: 0.088 inches Nut Style: Blind rivet w/smooth round shank Nut Diameter: Between 0.486 inches and 0.490 inches Nut Length: Between 1.360 inches and 1.390 inches Unable To Decode: 40.115 to 0.200 inches Hard Type: Closed Thread Series: Unf Thready Cty Per Inch (tpi): 24 Stel comp 4037 or steel comp 8740 Material: Strake Treatment: Cadmium Quep-116, type 2, cl 3 federal specification single treatment response Sheft Life: Na Lif Of Measure: Inf Sheft Life: Na Darder Treatment Specification single treatment response Sheft Life: Na Lif Of Measure: Inf Sheft Life: Na Life: Na Life: Na Life:	Head Style:
Between 0.766 inches and 0.796 inches Head Height: 0.088 inches Nut Style: Bilnd rivet w/smooth round shank Nut Diameter: Between 0.486 inches and 0.490 inches Nut Length: Between 1.360 inches and 1.390 inches Value To Decode: +0.115 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thread Series: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Shelf Life: Nate Qu-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: Na Unt Of Measure:	Flat
Head Height: 0.088 inches Nut Style: Blind rivet w/smooth round shank Nut Diameter: Between 0.486 inches and 0.490 inches Nut Length: Between 1.360 inches and 1.390 inches Unable To Decode: +0.115 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thread Series: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment: Qrap-416, type 2, d 3 federal specification single treatment response Shelf Life: N/a Unt Of Measure:	Head Diameter:
0.088 inches Nut Style: Bind rivet w/smooth round shank Nut Diameter: Between 0.486 inches and 0.490 inches Nut Length: Between 1.360 inches and 1.390 inches Unable To Decode: +0.115 to 0.200 inches Stank End Type: Closed Thread Series: Unf Thread Size: 0.375 inches Material Stel comp 4037 or stel comp 8740 Material Specification: Asia san standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Qap-416, type 2, ol 3 federal specification single treatment response Na SurfaceTreatment: Na Dint of Measure: Na Fig:	Between 0.766 inches and 0.796 inches
Nut Style: Bind rivet w/smooth round shank Nut Diameter: Between 0.486 inches and 0.490 inches Nut Length: Between 1.360 inches and 1.390 inches Vut Length: Between 1.360 inches and 1.390 inches Vut Length: Holde To Decode: +0.115 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thread Size: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Asia asen standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmim Material Guine Auge-116, type 2, cl 3 federal specification single treatment response Material Na Hord Measure: Na Store (Treatment Specification single treatment response Third Measure: Na Store (Store (Stor	Head Height:
Bind rivet w/smooth round shank Nut Diameter: Between 0.486 inches and 0.490 inches Nut Length: Between 1.360 inches and 1.390 inches Unable To Decode: 40.115 to 0.200 inches Bhark End Type: Closed Thread Series: Unf Thread System 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Pare-116, type 2, cl 3 federal specification single treatment response Surface Treatment: Na Surface Treatment: Pare-116, type 2, cl 3 federal specification single treatment response Material: Na Hit of Measure: Na Na Na Pare-116, type 2, cl 3 federal specification single treatment response Field Life: Na Field Life: Na Field Life: Na Steel Compilantization	0.088 inches
Nut Diameter: Between 0.486 inches and 0.490 inches Nut Length: Between 1.360 inches and 1.390 inches Unable To Decode: +0.115 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thread Series: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Q-q-+16, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: - Pomilitarization: Na Fig:	Nut Style:
Between 0.486 inches and 0.490 inches Nut Length: Between 1.360 inches and 1.390 inches Unable To Decode: +0.115 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification: Aq-p-416, type 2, d 3 federal specification single treatment response Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Blind rivet w/smooth round shank
Nut Length:Between 1.360 inches and 1.390 inchesUnable To Decode:40.115 to 0.200 inchesShank End Type:ClosedThread Series:UnfThread Series:24Thread Size:0.375 inchesMaterial:24Stel comp 4037 or steel comp 8740Material Specification:Aisi asen standard 1st material response or mil-s-6049 military specification 2nd material responseParface Treatment:CadmiumSurface Treatment Specification single treatment responseParf Life:N/aInit of Measure:Init of Measure:Init of Measure:NaFig:NaFig:NaSurface Treatment:Surface Treatment:Surface Treatment Specification single treatment responseSurface Treatment:NaSurface Treatment:Surface	Nut Diameter:
Between 1.360 inches and 1.390 inches Unable To Decode: +0.115 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification: Qup-416, type 2, cl 3 federal specification single treatment response Sheff Life: N/a Unit Of Measure: - Femilitarization: No Fig:	Between 0.486 inches and 0.490 inches
Unable To Decode: +0.115 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification single treatment response Sheff Life: N/a Unit Of Measure: - Demilitarization: No	Nut Length:
+0.115 to 0.200 inches Shank End Type: Closed Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification Aig-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 1.360 inches and 1.390 inches
Shank End Type:ClosedFiread Series:UnfFiready Qty Per Inch (tpi):24Fhread Size:0.375 inchesMaterial:Steel comp 4037 or steel comp 8740Material Specification:Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material responseFurface Treatment:CadmiumSurface Treatment Specification single treatment responseAng-p416, type 2, cl 3 federal specification single treatment responseShelf Life:IvaInti Of Measure:Imiliarization:NaFig:	Unable To Decode:
Closed Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification: Qu-p-416, type 2, cl 3 federal specification single treatment response Fuel Life: N/a Inti Of Measure: - Pomilitarization: Na Fig:	+0.115 to 0.200 inches
Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Shank End Type:
UnfThready Qty Per Inch (tpi):24Thread Size:0.375 inchesMaterial:Steel comp 4037 or steel comp 8740Material Specification:Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material responseSurface Treatment:CadmiumSurface Treatment Specification:Qu-p-416, type 2, cl 3 federal specification single treatment responsePheff Life:N/aInti Of Measure:Pomilitarization:NoFig:	Closed
Thready Qty Per Inch (tpi): 24 Thread Size: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Thread Series:
24 Thread Size: 0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Unf
Thread Size:0.375 inchesMaterial:Steel comp 4037 or steel comp 8740Material Specification:Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material responseSurface Treatment:CadmiumSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment responseShelf Life:N/aInit Of Measure:Demilitarization:NoFig:	Thready Qty Per Inch (tpi):
0.375 inches Material: Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Sheff Life: N/a Unit Of Measure: Demilitarization: No	24
Material:Steel comp 4037 or steel comp 8740Material Specification:Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material responseSurface Treatment:CadmiumCadmiumSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment responseShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	Thread Size:
Steel comp 4037 or steel comp 8740 Material Specification: Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.375 inches
Material Specification:Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material responseSurface Treatment:CadmiumCadmiumSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment responseShelf Life:N/aUnit Of Measure:-NoFig:	Material:
Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Pemilitarization: No	Steel comp 4037 or steel comp 8740
Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No	Material Specification:
Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Aisi assn standard 1st material response or mil-s-6049 military specification 2nd material response
Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:
Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig:	Qq-p-416, type 2, cl 3 federal specification single treatment response
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A021a0	Fiig:
	A021a0

NSN 5310-00-046-7486

Blind Rivet Plain Nut - Page 2 of 2

Mil-std (military Standard):

Mil-s-6049 spec.

