NSN 5310-00-064-1849

Hexagon Self-locking Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-064-1849

3b Firead Direction: Right-hand Locking Feature: Prevailing torque with nonmetallic insert Lubrication: Subble bubbles Prevailing torque with nonmetallic insert Lubrication: Subble bubbles Prevailing torque with nonmetallic insert Lubrication: Nur Style: Heasagon Nur Height: Between 0.133 inches and 0.157 inches With Across Flats: Between 0.251 inches Between 0.251 inches Porter Statis 260.0 degrees fabriconheit Thread Statis 250.0 degrees fabriconheit Orlog: Thread Statis Statis Angle: 2010 Thread Statis 2011 Statis Angle: 2012 Charler of washer faced Bearing Surface Tpine: 215.0 microinches Materi Couper alloy 360 nut or copper alloy 260 nut Surface Teation Que per alloy 360 nut or copper alloy 260 nut Surface T	Thread Class:
Tread Direction: Right-hand Locking Feature: Prevailing torque with nonmetallic insert Lubrication: Soluble lubricant Nut Style: Hexagon Nut Height: Between 0.243 inches and 0.157 inches With Across Flats: Between 0.243 inches and 0.251 inches Thread Size: 0.130 inches and 0.251 inches Thread Size: 0.14 inches Thread Size: 0.12 inches 0.12 inches Bearing Surface Type: 12.5.0 incroinches Matter Coperating Soft out or copper alloy 260 nut Surface Treatments Copperating Soft out or copper alloy 260 nut Surface Treatments Copperating Soft out cropper alloy 260 nut Surface Treatments Cadmium except insert Surface Treatment Specification Na Nature Nature Surface Treatment Specification single treatment response except insert Surface Treatment Specification single treatment response except insert Nature Na	
Right-hand Locking Feature: Prevailing torque with nonmetallic insert Lubrication: Soluble lubricant Nut Style: Hexagon Nut Height: Between 0.133 inches and 0.157 inches Witth Across Flats: Between 0.243 inches and 0.251 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unje Thread Series: 0.132 8.0 degrees nut 8.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Tinish: 125.0 nicroinches Materiat: Capera alloy 360 nut or copper alloy 260 nut Surface Treatment: Capera licy 31 defear la specification single treatment response except insert Sher Lie: Na Variat Chot Messure: Na Surface Tinish: 125.0 nicroinches Materiat: Caperatio, the defear la specification single treatment response except insert Surface Treatment Specification single tre	
Locking Feature: Prevailing torque with nonmetallic insert Lubrication: Soluble lubricant Nul Style: Hexagon Nut Height: Between 0.133 Inches and 0.157 Inches With Across Flats: Between 0.243 Inches and 0.251 Inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unje Thread Series: Unge 8.0 degrees nut 8.0 degrees nut Bearing Surface Traise: 125.0 nicroinches Meried: Coutersink Angle: 8.0 degrees nut Bearing Surface Traise: 125.0 nicroinches Material: Coper alloy 360 nut or copper alloy 260 nut Surface Traisent Cadmium except insert Surface Traisent Que-Alf, type 2, of 3 dederal specification single treatment response except insert Na Lubrick Na Surface Traisent Gardinie accept insert Surface Traisent Na	
Prevailing torque with nonmetallic insert Lubrication: Soluble lubricant Nut Style: Hexagon Nut Height: Between 0.133 inches and 0.157 inches Width Across Flats: Between 0.243 inches and 0.251 inches Temparture Rating: 250.0 degrees fahrenheit Thread Series: Unje Thread Stree: 0.112 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Charlered Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment Cadmium except insert Surface Treatment Cadmium except insert Na Surface Treatment Cadmium except insert Surface Cadmium except insert Cadmium excep	-
Lubrication: Soluble lubricant Hexagon Nut Height: Between 0.133 inches and 0.157 inches With Across Flats: Between 0.243 inches and 0.251 inches Torparture Rating: 250.0 degrees fahrenheit Thread Series: Unje Toread Series: 0.112 inches Gougrees nut Solud egrees nut Bearing Surface Traish: 152.0 degrees nut Bearing Surface Traish: 152.0 microinches Materiel Countersink Angle: 152.0 microinches Bearing Surface Traish: 152.0 microinches Materiel Couper alloy 360 nut or copper alloy 260 nut Carder Treatment: Query Instruction: Query Instruction: Query Instruction: Query Instruction: Query Instruction: Definition And Instruction: Definition And Instruction: Definition And Instruction: Definition And Instruction: Definiting:	
Solubie lubricant Nut Style: Hexagon Nut Height: Between 0.133 inches and 0.157 inches Between 0.243 inches and 0.251 inches Tempurature Rating: Edouden 2.43 inches and 0.251 inches Tempurature Rating: Edouden Striss: Unip Thread Striss: Unip Thread Striss: Unip Thread Striss: Unip Chardier Striss: Edouden Striss: Ed	
Nut Siyle: Hexagon Nut Height: Between 0.133 inches and 0.157 inches With Across Flats: Between 0.243 inches and 0.251 inches Tompurture Rating: 250.0 degrees fahrenheit Thread Series: Unjo Thread Series: 0.112 inches 60.0 0.112 inches Betreers nut Betreers nut Betring Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 discouncienches Materia! Copper alloy 260 nut or copper alloy 260 nut Surface Treatment Cadmium except insert Aufort Vare Parifice Treatment Specification Quep-416, type 2, of 3 federal specification single treatment response except insert Surface Treatment Specification Na Parification: Na Surface Treatment Specification Surface Treatment Specification Parification: Na Surface Treatment Specification Na	
Hexagon Nut Height: Between 0.133 inches and 0.157 inches With Across Flats: Between 0.243 inches and 0.251 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unje Thread Stell 0.112 inches 0.112 inches 0.112 inches Batogenes nut Batogenes nut Batogenes nut Batogenes nut Demired or washer faced Bering Surface Finish: 12.5 on incrinches Material Copper alloy 260 nut or copper alloy 260 nut Surface Treatment Cadmium except insert Auge-418, type 2, d 3 federal specification single treatment response except insert Pariel Na Pariel Messure: Imaterial Messure: Imaterial Messure: Imaterial Messure: Pariel Messure: Imaterial Messure: Imaterial Messure: Imaterial Messure: Batogenes nut Batogenes nut Imaterial Messure: <tr< td=""><td></td></tr<>	
Nut Height: Between 0.133 inches and 0.157 inches Width Across Flats: Between 0.243 inches and 0.251 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unip: Thread Surjes: 0.112 inches 0.112 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chanfered or washer faced Bearing Surface Finish: 125.0 microinches Matterial: Capper alloy 360 nut or copper alloy 260 nut Surface Treatment: Capher 1, type 2, d 3 federal specification single treatment response except insert Surface Treatment Specification: Na Material: Na Id O Measure: Na Na Na Na Na Na Na Na Surface Treatment Specification: Na Naterial: Naterial: Naterial: Naterial:	
Between 0.133 inches and 0.157 inches Width Across Flats: Between 0.243 inches and 0.251 inches Tompurature Rating: 250.0 degrees fahrenheit Thread Series: Unjo Thread Surjes: 0.101 A0 Thread Size: 0.112 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Type: Contersink Angle: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Surface Treatment Specification Na Natrial:	
Width Across Flats: Between 0.243 inches and 0.251 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unje Thready Qty Per Inch (tpl): 40 Thread Size: 0.112 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Quep-416, type 2, d 3 federal specification single treatment response except insert Naterial: Naterial: Naterial: Naterial: Quep-416, type 2, d 3 federal specification single treatment response except insert Sheft Life: Naterial: Naterial: Int Of Measure: Int Of Measure: <t< td=""><td></td></t<>	
Between 0.243 inches and 0.251 inches Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unjc Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Countersink Angle: 83.0 degrees nut Bearing Surface Type: Chamferd or washer faced Bearing Surface Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Gradmium except insert Nate Ider Of Measure: Nate Dut Of Measure: Nate Fig:	
Empurature Rating: 250.0 degrees fahrenheit Thread Series: Unjc Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Cooper alloy 360 nut or copper alloy 260 nut Surface Treatment: Qacy-140, type 2, d 3 federal specification single treatment response except insert Surface Treatment Specification Na Pint of Measure: - - Fig:	
250.0 degrees fahrenheit Firead Series: Unic Fiready Qty Per Inch (tpi): 40 Fiready Qty Per Inch (tpi): 40 Firead Size: 6.112 inches 6.112 inches 6.112 inches 6.20 degrees nut 6.20 degrees nut 6.20 degrees nut 7.20	
Threads Series: Unjo Thready Cyp Per Inch (tpi): 40 Thread Size: 0.112 Inches Countersink Angle: 8.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment Qap-416, type 2, ol 3 federal specification single treatment response except insert Surface Treatment Specification Init of Measure: Image: No Fig:	
Unic Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Coutersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Qrap-416, type 2, dl 3 federal specification single treatment response except insert Pairle Na Init Of Measure: r Pomilitarization: No Fig:	
Tready Qty Per Inch (tpi): 40 Thread Size: 0.112 Inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment Pacification: Quep-416, type 2, cl 3 federal specification single treatment response except insert Shelf Life: Na Int of Measure: Image: No Fig:	
40Thread Size:0.112 inchesCountersink Angle:88.0 degrees nutBearing Surface Type:Chamfered or washer facedBearing Surface Finish:125.0 microinchesMaterial:Copper alloy 360 nut or copper alloy 260 nutSurface Treatment:Cadmium except insertSurface Treatment Specification single treatment response except insertSheft Life:N/aIn of Measure:Image:NaFing:NaFing:NaNaImage:NaImage:NaImage:NaImage:NaSurface:Image:Ima	
Thread Size: 0.112 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Surface Treatment Specification Q-p-416, type 2, cl 3 federal specification single treatment response except insert Shelf Life: N/a Int of Measure: - - Pomilitarization: No Fig:	
0.112 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Cadmium except insert Surface Treatment Specification Qr-p-116, type 2, d 3 federal specification single treatment response except insert Shelf Life: N/a Mit Of Measure: Fig:	
Countersink Angle:88.0 degrees nutBearing Surface Type:Chamfered or washer facedBearing Surface Finish:125.0 microinchesMaterial:Copper alloy 360 nut or copper alloy 260 nutSurface Treatment:Cadmium except insertPurface Treatment SpecificationQrq-P416, type 2, cl 3 federal specification single treatment response except insertShelf Life:N/aInit Of Measure:NaFig:	
88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Surface Treatment Specification Q-q416, type 2, cl 3 federal specification single treatment response except insert Shelf Life: N/a Juit Of Measure: - No Fig:	
Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Cadmium except insert Surface Treatment Specification Qq-p-416, type 2, cl 3 federal specification single treatment response except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No	-
Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Cadmium except insert Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Bearing Surface Finish:125.0 microinchesMaterial:Copper alloy 360 nut or copper alloy 260 nutSurface Treatment:Cadmium except insertSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment response except insertShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
125.0 microinches Material: Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Cadmium except insert Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Material:Copper alloy 360 nut or copper alloy 260 nutSurface Treatment:Cadmium except insertCadmium except insertSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment response except insertShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
Copper alloy 360 nut or copper alloy 260 nut Surface Treatment: Cadmium except insert Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Surface Treatment:Cadmium except insertSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment response except insertShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
Cadmium except insert Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Qq-p-416, type 2, cl 3 federal specification single treatment response except insert Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
Demilitarization: No Fiig:	
No Fiig:	
Fiig:	
A021a0	A021a0