

View Online at <https://aerobasegroup.com/nsn/5310-00-067-4901>

**Thread Pitch Diameters:**

+0.4487/+0.4513 inches

**Thread Direction:**

Right-hand

**Drive Point Depth:**

0.062 inches

**Nut Style:**

Round

**Nut Diameter:**

Between 0.855 inches and 0.885 inches

**Nut Thickness:**

Between 0.303 inches and 0.323 inches

**Drive Point Width:**

Between 0.120 inches and 0.130 inches

**Drive Point Quantity:**

4

**Thread Series:**

Uns

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

Between 66.0 rockwell b and 92.0 rockwell b

**Thread Size:**

0.469 inches

**Material:**

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1034 or steel comp 1035

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification 1st treatment response or qq-z-325 type 2 cl 3 federal specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0