

View Online at <https://aerobasegroup.com/nsn/5310-00-083-9303>

Hole Diameter:

Between 0.252 inches and 0.258 inches

Radius:

Between 0.235 inches and 0.240 inches

Outside Diameter:

Between 0.375 inches and 0.385 inches

Recess Depth:

Between 0.040 inches and 0.050 inches

Material Thickness:

Between 0.078 inches and 0.088 inches

Hardness Rating:

Between 38.0 rockwell c and 44.0 rockwell c

Surface Finish:

63.0 microinches counterbore wall

Heat Treatment:

As fabricated

Material:

Steel comp 8740 or steel comp 8630 or steel comp 4130 or steel comp 4027

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6758 military specification 3rd material response or mil-s-18729 military specification 3rd material response or astm a322 assn standard 4th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Concave

Specification Data:

81205-bacw10au manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0

Mil-std (military Standard):

Mil-s-6049 spec.