

View Online at <https://aerobasegroup.com/nsn/5310-00-110-7184>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Small End Diameter:**

Between 1.790 inches and 1.810 inches

**Drive Point Depth:**

0.156 inches

**Nut Style:**

Round

**Nut Diameter:**

Between 2.177 inches and 2.197 inches

**Nut Thickness:**

Between 0.495 inches and 0.505 inches

**Drive Point Width:**

0.188 inches

**Undercut Thickness:**

0.300 mils and 0.310 centimeters

**Drive Point Quantity:**

8

**Drilled Hole Diameter:**

0.144 inches

**Hole Type And Quantity:**

8 drilled

**Thread Series:**

Unef

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

Between 34.0 rockwell c and 38.0 rockwell c

**Thread Size:**

1.375 inches

**Hole Configuration Style:**

Configuration f

**Countersink Angle:**

85.0 degrees second end and 95.0 degrees second end

**Special Features:**

Eight equally spaced holes 0.266 in. Diameter by 0.040 in. Deep drilled on flat surface between drive points on 1.700 in. Diameter circle, max surface fini sh, small end diameter 63 microinches aa, all others 90 microinches aa

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-5000, condition c military standard single material response

**Surface Treatment:**

Cadmium or lacquer acrylic

**Surface Treatment Specification:**

Qq-p-416 class 2, type 2 or 3 assn standard single treatment response or mil-l-1 assn standard single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-s-5000 spec.