

View Online at <https://aerobasegroup.com/nsn/5310-00-110-7184>

Thread Class:

3b

Thread Direction:

Right-hand

Small End Diameter:

Between 1.790 inches and 1.810 inches

Drive Point Depth:

0.156 inches

Nut Style:

Round

Nut Diameter:

Between 2.177 inches and 2.197 inches

Nut Thickness:

Between 0.495 inches and 0.505 inches

Drive Point Width:

0.188 inches

Undercut Thickness:

0.300 mils and 0.310 centimeters

Drive Point Quantity:

8

Drilled Hole Diameter:

0.144 inches

Hole Type And Quantity:

8 drilled

Thread Series:

Unef

Thready Qty Per Inch (tpi):

18

Hardness Rating:

Between 34.0 rockwell c and 38.0 rockwell c

Thread Size:

1.375 inches

Hole Configuration Style:

Configuration f

Countersink Angle:

85.0 degrees second end and 95.0 degrees second end

Special Features:

Eight equally spaced holes 0.266 in. Diameter by 0.040 in. Deep drilled on flat surface between drive points on 1.700 in. Diameter circle, max surface fini sh, small end diameter 63 microinches aa, all others 90 microinches aa

Material:

Steel comp 4340

Material Specification:

Mil-s-5000, condition c military standard single material response

Surface Treatment:

Cadmium or lacquer acrylic

Surface Treatment Specification:

Qq-p-416 class 2, type 2 or 3 assn standard single treatment response or mil-l-1 assn standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-5000 spec.