## NSN 5310-00-131-2665

Flat Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-131-2665

Rectangular  Hole Diameter: Between 0.252 inches and 0.258 inches  Edge Shape: Round  Center Hole Shape: Round  Thickness: 0.063 inches  Overall Diameter: Between 0.495 inches and 0.520 inches  Min. Tensile Strength (psi): 55000 pounds per square inch  Surface Finish: 32.0 microinches bottom  Material: Steel or steel comp 1018 or steel comp 4130  Material Specification: Mill-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mill-s-18729, cond n military specification 3rd material response  Shelf Life: N/a
Between 0.252 inches and 0.258 inches  Edge Shape: Round  Center Hole Shape: Round  Thickness: 0.063 inches  Overall Diameter: Between 0.495 inches and 0.520 inches  Min. Tensile Strength (psi): 55000 pounds per square inch  Surface Finish: 32.0 microinches bottom  Material: Steel or steel comp 1018 or steel comp 4130  Material Specification: Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life: N/a
Edge Shape:  Round  Center Hole Shape: Round  Thickness: 0.063 inches  Overall Diameter:  Between 0.495 inches and 0.520 inches  Min. Tensile Strength (psi): 55000 pounds per square inch  Surface Finish: 32.0 microinches bottom  Material:  Steel or steel comp 1018 or steel comp 4130  Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life: N/a
Round  Center Hole Shape: Round  Thickness: 0.063 inches  Overall Diameter: Between 0.495 inches and 0.520 inches  Min. Tensile Strength (psi): 55000 pounds per square inch  Surface Finish: 32.0 microinches bottom  Material: Steel or steel comp 1018 or steel comp 4130  Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life: N/a
Center Hole Shape: Round Thickness: 0.063 inches Overall Diameter: Between 0.495 inches and 0.520 inches Min. Tensile Strength (psi): 55000 pounds per square inch Surface Finish: 32.0 microinches bottom Material: Steel or steel comp 1018 or steel comp 4130 Material Specification: Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response Shelf Life: N/a
Round Thickness: 0.063 inches Overall Diameter: Between 0.495 inches and 0.520 inches Min. Tensile Strength (psi): 55000 pounds per square inch Surface Finish: 32.0 microinches bottom Material: Steel or steel comp 1018 or steel comp 4130 Material Specification: Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response Shelf Life: N/a
Thickness:  0.063 inches  Overall Diameter:  Between 0.495 inches and 0.520 inches  Min. Tensile Strength (psi):  55000 pounds per square inch  Surface Finish:  32.0 microinches bottom  Material:  Steel or steel comp 1018 or steel comp 4130  Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life:  N/a
Overall Diameter:  Between 0.495 inches and 0.520 inches  Min. Tensile Strength (psi):  55000 pounds per square inch  Surface Finish:  32.0 microinches bottom  Material:  Steel or steel comp 1018 or steel comp 4130  Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life:  N/a
Overall Diameter:  Between 0.495 inches and 0.520 inches  Min. Tensile Strength (psi):  55000 pounds per square inch  Surface Finish:  32.0 microinches bottom  Material:  Steel or steel comp 1018 or steel comp 4130  Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life:  N/a
Between 0.495 inches and 0.520 inches  Min. Tensile Strength (psi):  55000 pounds per square inch  Surface Finish:  32.0 microinches bottom  Material:  Steel or steel comp 1018 or steel comp 4130  Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life:  N/a
Min. Tensile Strength (psi): 55000 pounds per square inch Surface Finish: 32.0 microinches bottom Material: Steel or steel comp 1018 or steel comp 4130 Material Specification: Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response Shelf Life: N/a
55000 pounds per square inch  Surface Finish:  32.0 microinches bottom  Material:  Steel or steel comp 1018 or steel comp 4130  Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life:  N/a
Surface Finish:  32.0 microinches bottom  Material:  Steel or steel comp 1018 or steel comp 4130  Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life:  N/a
32.0 microinches bottom  Material:  Steel or steel comp 1018 or steel comp 4130  Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life:  N/a
Material: Steel or steel comp 1018 or steel comp 4130  Material Specification: Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life: N/a
Steel or steel comp 1018 or steel comp 4130  Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life:  N/a
Material Specification:  Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life:  N/a
Mil-s-7952 military specification 1st material response and aisi assn standard 2nd material response and mil-s-18729, cond n military specification 3rd material response  Shelf Life:  N/a
specification 3rd material response  Shelf Life: N/a
Shelf Life: N/a
N/a
Heit Of Magazine
Unit Of Measure:
Demilitarization:
No
Fiig:
A022b0
Mil-std (military Standard):
Mil-s-7952 spec.