NSN 5310-00-138-0103

Flat Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-138-0103

Rectangular Hole Diameter: Between 0.315 inches and 0.322 inches	
Petuson 0.215 inches and 0.222 inches	
Detween 0.3 to inches and 0.322 inches	
Edge Shape:	
Round	
Center Hole Shape:	
Round	
Thickness:	
Between 0.120 inches and 0.130 inches	
Overall Diameter:	
Between 0.548 inches and 0.578 inches	
Min. Tensile Strength (psi):	
125000 pounds per square inch	
Material:	
Steel comp 1025 or steel comp 4130 or steel comp 8630	
Material Specification:	
Mil-t-5066 military specification 1st material response or mil-s-6758 cond f military specification 2nd material response or mil-s-	-6050 cond f
military specification 3rd material response or mil-t-6732 type 1 cond ht-125 military specification 3rd material response	
Surface Treatment:	
Cadmium	
Surface Treatment Specification:	
Qq-p-416, type 2, cl 2 federal specification single treatment response	
Specification Data:	
80205-nas42 professional/industrial association standard	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A022b0	
Mil-std (military Standard):	
Mil-t-5066 spec.	