NSN 5310-00-138-6625

Sleeve Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-138-6625

| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Flange Thickness: |
| 0.382 inches |
| Nut Style: |
| Sleeve |
| Nut Diameter: |
| 1.118 inches |
| Nut Length: |
| 0.430 inches |
| Flange Width Across Flats: |
| Between 1.109 inches and 1.127 inches |
| Drilled Hole Diameter: |
| 0.070 inches |
| Hole Type And Quantity: |
| 3 drilled |
| Cross-sectional Shape: |
| Round nut |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 16 |
| Hardness Rating: |
| Between 34.0 rockwell c and 38.0 rockwell c |
| Thread Size: |
| 0.750 inches |
| Hole Configuration Style: |
| Configuration b |
| Countersink Angle: |
| 90.0 degrees nut |
| Material: |
| Steel comp 4130 |
| Material Specification: |
| Mil-s-6758 military specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Shelf Life: |
| N/a |

NSN 5310-00-138-6625

Sleeve Nut - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-6758 spec.