NSN 5310-00-145-2012

Blind Rivet Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-145-2012

| Thread Class: | | | | | |
|---|--|--|--|--|--|
| 3b | | | | | |
| Thread Direction: | | | | | |
| | | | | | |
| Right-hand | | | | | |
| Head Style: | | | | | |
| Flat countersunk reverse keyed Head Diameter: | | | | | |
| 0.391 inches | | | | | |
| Key Length: | | | | | |
| 0.065 inches | | | | | |
| Head Height: | | | | | |
| 0.065 inches | | | | | |
| Nut Style: | | | | | |
| Blind rivet w/smooth round shank | | | | | |
| Nut Diameter: | | | | | |
| Between 0.246 inches and 0.250 inches | | | | | |
| Nut Length: | | | | | |
| Between 0.969 inches and 0.999 inches | | | | | |
| Unable To Decode: | | | | | |
| +0.216 to 0.266 inches | | | | | |
| Shank End Type: | | | | | |
| Closed | | | | | |
| Thread Series: | | | | | |
| Unf | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 32 | | | | | |
| Thread Size: | | | | | |
| 0.190 inches | | | | | |
| Head Countersink Angle: | | | | | |
| Between 99.00 degrees and 101.00 degrees | | | | | |
| Material: | | | | | |
| Aluminum alloy 6053 | | | | | |
| Material Specification: | | | | | |
| Mil-r-1150 military specification single material response | | | | | |
| Surface Treatment: | | | | | |
| Anodize | | | | | |
| Surface Treatment Specification: | | | | | |
| Mil-a-8625, type 2 military specification single treatment response | | | | | |
| Specification Data: | | | | | |
| 80205-nas1330 professional/industrial association standard | | | | | |
| Shelf Life: | | | | | |

N/a

NSN 5310-00-145-2012

Blind Rivet Plain Nut - Page 2 of 2



| | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-r-1150 spec.