## NSN 5310-00-151-5430

Assembled Washer Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-151-5430 **Thread Class: Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Washer Outside Diameter:** Between 0.610 inches and 0.640 inches **Counterbore Diameter:** 0.385 inches nut and 0.395 inches nut **Overall Height:** Between 0.396 inches and 0.436 inches **Nut Style:** Flat with turned back edge **Nut Height:** 0.203 inches **Nut Counterbore Depth:** 0.203 inches nut and 0.223 inches nut Width Across Flats: Between 0.492 inches and 0.502 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unjf Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Countersink Angle:** 60.0 degrees nut Material: Steel comp 1137 nut or steel comp 11137 nut or steel comp 8740 nut **Material Specification:** Qq-a-225/6, t4 federal specification 1st material response washer or qq-a-250/13, t6 federal specification 2nd material response washer **Surface Treatment:** Cadmium nut and chromate nut **Surface Treatment Specification:** Mil-c-5541 military specification single treatment response washer Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5310-00-151-5430

Assembled Washer Self-locking Nut - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-c-5541 spec.