

View Online at https://aerobasegroup.com/nsn/5310-00-159-9547

Thread Class:	
3b	
Thread Direction:	
Right-hand	
Locking Feature:	
Prevailing torque all m	
Washer Outside Diar	neter:
0.560 inches	
Counterbore Diamet	
0.342 inches nut and	0.352 inches nut
Verall Height:	
etween 0.316 inches	and 0.336 inches
Nut Style:	
lat with turned up ed	
lut Counterbore Dep	
0.072 inches nut and	0.087 inches nut
Vidth Across Flats:	
Between 0.367 inches	and 0.376 inches
hread Series:	
Jnjf	
Thready Qty Per Incl	(tpi):
28	
lardness Rating:	
etween 36.0 rockwe	c and 40.0 rockwell c
hread Size:	
.250 inches	
laterial:	
steel comp e4340 nut	or steel comp 4340 nut or steel comp 8740 nut
laterial Specificatio	
/lil-s-5000 military spe	cification 1st material response nut or mil-s-5000 military specification 2nd material response nut or mil-s-6049 military
pecification 3rd mate	ial response nut
Surface Treatment:	
Cadmium	
Surface Treatment S	pecification:
⊋q-p-416, type 2, cl େ	federal specification single treatment response
Shelf Life:	
N/a	
Jnit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
-	



Mil-std (military Standard):

Mil-s-5000 spec.