

View Online at <https://aerobasegroup.com/nsn/5310-00-164-7901>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Distance From Centerline To Flat:**

0.211 inches

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.194 inches nut

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate

**Nut Length:**

0.556 inches

**Nut Height:**

0.227 inches

**Plate Thickness:**

0.035 inches

**Plate Width:**

0.492 inches

**Nut Counterbore Depth:**

0.062 inches nut

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.245 inches and 0.255 inches

**Center To Center Distance Between Mounting Holes Along Width:**

Between 0.217 inches and 0.221 inches

**Tempurature Rating:**

450.0 degrees fahrenheit

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Material:**

Steel comp 1536 or steel comp 1541 or steel comp 1548 or steel comp 1552

**Material Specification:**

Sae assn standard all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Specification Data:**

81205-bac-10kh manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0