Plate Self-locking Nut - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5310-00-176-6731



| hread Class:   |
|--|
| b  |
| hread Direction:   |
| light-hand   |
| ocking Feature:  |
| revailing torque all metal design                            |
| lounting Hole Diameter:                                      |
| etween 0.098 inches and 0.103 inches                         |
| lut Style:   |
| late   |
| lut Length:  |
| etween 0.923 inches and 0.948 inches                         |
| lut Height:  |
| .270 inches  |
| late Thickness:  |
| .031 inches  |
| late Width:  |
| .453 inches  |
| lut Mounting Provision:                                      |
| traight holes  |
| Iounting Hole Arrangement Style:                             |
| holes  |
| istance From Aperture Center To Mounting Hole Center:        |
| etween 0.339 inches and 0.349 inches                         |
| center To Center Distance Between Mounting Holes Along Lengt |
| etween 0.686 inches and 0.690 inches                         |
| empurature Rating:   |
| 200.0 degrees fahrenheit                                     |
| hread Series:  |
| Inf  |
| hready Qty Per Inch (tpi):                                   |
| 2  |
| hread Size:  |
| .190 inches  |
| countersink Angle:   |
| 00.0 degrees nut   |
| roduct Name:   |
| lavy special project   |
| pecial Features:   |
| Curved base 1.5 in. Radius                                   |
| laterial:  |
| on alloy 660   |
|  |

## NSN 5310-00-176-6731

Plate Self-locking Nut - Page 2 of 2



Material Specification:

Ams 5525 assn standard single material response

**Precious Material:** 

Silver

Surface Treatment:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0