NSN 5310-00-177-7662

Blind Rivet Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-177-7662

| Thread Class: | | | | | | |
|--|--|--|--|--|--|--|
| 3b | | | | | | |
| Thread Direction: | | | | | | |
| Right-hand | | | | | | |
| Head Style: | | | | | | |
| Flat countersunk reverse keyed | | | | | | |
| Head Diameter: | | | | | | |
| 0.355 inches | | | | | | |
| Key Length: | | | | | | |
| 0.063 inches | | | | | | |
| Head Height: | | | | | | |
| 0.063 inches | | | | | | |
| Nut Style: | | | | | | |
| Blind rivet w/smooth round shank | | | | | | |
| Nut Diameter: | | | | | | |
| Between 0.217 inches and 0.221 inches | | | | | | |
| Nut Length: | | | | | | |
| Between 0.547 inches and 0.577 inches | | | | | | |
| Unable To Decode: | | | | | | |
| +0.161 to 0.201 inches | | | | | | |
| Shank End Type: | | | | | | |
| | | | | | | |
| Open | | | | | | |
| Open Thread Series: | | | | | | |
| • | | | | | | |
| Thread Series: | | | | | | |
| Thread Series: Unc | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches Head Countersink Angle: | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches Head Countersink Angle: Between 99.00 degrees and 101.00 degrees | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches Head Countersink Angle: Between 99.00 degrees and 101.00 degrees Material: | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches Head Countersink Angle: Between 99.00 degrees and 101.00 degrees Material: Steel comp 1108 or steel comp 1110 | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches Head Countersink Angle: Between 99.00 degrees and 101.00 degrees Material: Steel comp 1108 or steel comp 1110 Material Specification: | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches Head Countersink Angle: Between 99.00 degrees and 101.00 degrees Material: Steel comp 1108 or steel comp 1110 Material Specification: Qq-w-405 federal specification all material responses | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches Head Countersink Angle: Between 99.00 degrees and 101.00 degrees Material: Steel comp 1108 or steel comp 1110 Material Specification: Qq-w-405 federal specification all material responses Surface Treatment: | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches Head Countersink Angle: Between 99.00 degrees and 101.00 degrees Material: Steel comp 1108 or steel comp 1110 Material Specification: Qq-w-405 federal specification all material responses Surface Treatment: Cadmium | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches Head Countersink Angle: Between 99.00 degrees and 101.00 degrees Material: Steel comp 1108 or steel comp 1110 Material Specification: Qq-w-405 federal specification all material responses Surface Treatment: Cadmium Surface Treatment Specification: | | | | | | |
| Thread Series: Unc Thready Qty Per Inch (tpi): 32 Thread Size: 0.164 inches Head Countersink Angle: Between 99.00 degrees and 101.00 degrees Material: Steel comp 1108 or steel comp 1110 Material Specification: Qq-w-405 federal specification all material responses Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response | | | | | | |

N/a

NSN 5310-00-177-7662

Blind Rivet Plain Nut - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A021a0