NSN 5310-00-185-6397

Round Plain Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-185-6397

Thread Pitch Diameters:
+0.6437/+0.6467 inches
Thread Direction:
Right-hand
Drive Point Depth:
0.094 inches
Nut Style:
Round
Nut Diameter:
Between 1.105 inches and 1.135 inches
Nut Thickness:
Between 1.110 inches and 1.130 inches
Drive Point Width:
Between 0.120 inches and 0.130 inches
Drive Point Quantity:
4
Thread Series:
Uns
Thready Qty Per Inch (tpi):
32
Hardness Rating:
Hardness Rating: Between 66.0 rockwell b and 92.0 rockwell b
Between 66.0 rockwell b and 92.0 rockwell b
Between 66.0 rockwell b and 92.0 rockwell b Thread Size:
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material:
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment:
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment: Cadmium
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment: Cadmium Surface Treatment Specification:
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Specification Or Standard:
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Specification Or Standard: 1 type and 3 class
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Specification Or Standard: 1 type and 3 class Shelf Life:
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Specification Or Standard: 1 type and 3 class Shelf Life: N/a
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Specification Or Standard: 1 type and 3 class Shelf Life: N/a
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Specification Or Standard: 1 type and 3 class Shelf Life: N/a Unit Of Measure:
Between 66.0 rockwell b and 92.0 rockwell b Thread Size: 0.664 inches Material: Steel comp 1005 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Specification Or Standard: 1 type and 3 class Shelf Life: N/a Unit Of Measure: Demilitarization: