

View Online at <https://aerobasegroup.com/nsn/5310-00-186-0977>

Hole Diameter:

Between 3.582 inches and 3.612 inches

Outside Diameter:

Between 4.281 inches and 4.326 inches

Internal Prebent Key Length:

Between 0.188 inches and 0.250 inches

External Prebent Key Width:

Between 0.298 inches and 0.328 inches

Internal Prebent Key Width:

Between 0.313 inches and 0.353 inches

Overall Distance Including Keys:

4.938 inches

External Key Quantity:

19

Material Thickness:

Between 0.088 inches and 0.100 inches

End Application:

W/s: supply class aoe; stream (std, tensioned replenishment at sea method); fms-knox class ff; whichbey island class lsd; systems, jp-5 aviation fuels; tarawa class lha; nimitz class cvn; trailer, semi (m860a1)

Hardness Rating:

Between 50.0 rockwell b and 81.0 rockwell b

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1025 or steel comp 1030 or steel comp 1035

Material Specification:

66 federal standard all material responses

Style Designator:

Key

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0