

View Online at <https://aerobasegroup.com/nsn/5310-00-186-0979>

**Hole Diameter:**

Between 3.988 inches and 4.018 inches

**Outside Diameter:**

Between 4.812 inches and 4.857 inches

**Internal Prebent Key Length:**

Between 0.250 inches and 0.312 inches

**External Prebent Key Width:**

Between 0.298 inches and 0.328 inches

**Internal Prebent Key Width:**

Between 0.313 inches and 0.353 inches

**Overall Distance Including Keys:**

5.500 inches

**External Key Quantity:**

19

**Material Thickness:**

Between 0.088 inches and 0.100 inches

**End Application:**

W/s: los angeles class ssn (688); nimitz class cvn; forrestal class cv; oliver perry class ffg; lighter amphibious sp, 60-ton, larc-lx; elevators, aircraft; ticonderonga class cg (47); spruance class dd (963); elevators, cargo/weapons

**Hardness Rating:**

Between 50.0 rockwell b and 81.0 rockwell b

**Material:**

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019

**Material Specification:**

Sae assn standard all material responses

**Style Designator:**

Key

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A022b0