

View Online at <https://aerobasegroup.com/nsn/5310-00-186-0979>

Hole Diameter:

Between 3.988 inches and 4.018 inches

Outside Diameter:

Between 4.812 inches and 4.857 inches

Internal Prebent Key Length:

Between 0.250 inches and 0.312 inches

External Prebent Key Width:

Between 0.298 inches and 0.328 inches

Internal Prebent Key Width:

Between 0.313 inches and 0.353 inches

Overall Distance Including Keys:

5.500 inches

External Key Quantity:

19

Material Thickness:

Between 0.088 inches and 0.100 inches

End Application:

W/s: los angeles class ssn (688); nimitz class cvn; forrestal class cv; oliver perry class ffg; lighter amphibious sp, 60-ton, larc-lx; elevators, aircraft; ticonderonga class cg (47); spruance class dd (963); elevators, cargo/weapons

Hardness Rating:

Between 50.0 rockwell b and 81.0 rockwell b

Material:

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019

Material Specification:

Sae assn standard all material responses

Style Designator:

Key

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0