NSN 5310-00-193-0555

Round Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-193-0555

| Thread Pitch Diameters: |
|--|
| +3.0750/+3.0803 inches |
| Thread Direction: |
| Right-hand |
| Flange Thickness: |
| 0.237 inches |
| Drive Point Depth: |
| 0.187 inches |
| Nut Style: |
| Round |
| Nut Diameter: |
| 3.656 inches |
| Nut Thickness: |
| 0.405 inches |
| Drive Point Width: |
| 0.375 inches |
| Drive Point Quantity: |
| 8 |
| Drilled Hole Diameter: |
| 0.125 inches |
| Hole Type And Quantity: |
| 8 drilled |
| Thread Series: |
| Buttress |
| Thready Qty Per Inch (tpi): |
| 12 |
| Hardness Rating: |
| Between 26.0 rockwell c and 33.0 rockwell c |
| Thread Size: |
| 3.125 inches |
| Hole Configuration Style: |
| Configuration f |
| Countersink Angle: |
| 90.0 degrees nut |
| Material: |
| Steel comp 4130 or steel comp 4340 |
| Material Specification: |
| Mil-s-6758, cond d military specification 1st material response or mil-s-5000 military specification 2nd material response |
| Surface Treatment: |
| Phosphate |
| Surface Treatment Specification |

Ss-8416, united aircraft corp, sikorsky aircraft div mfr ref single treatment response

NSN 5310-00-193-0555

Round Plain Nut - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| | |

Mil-std (military Standard):

Mil-s-6758 spec.

Shelf Life: