

View Online at <https://aerobasegroup.com/nsn/5310-00-205-8245>

**Hole Diameter:**

Between 1.193 inches and 1.213 inches

**Outside Diameter:**

Between 1.500 inches and 1.515 inches

**Internal Prebent Key Length:**

Between 0.094 inches and 0.125 inches

**External Prebent Key Width:**

Between 0.146 inches and 0.166 inches

**Internal Prebent Key Width:**

Between 0.156 inches and 0.176 inches

**Overall Distance Including Keys:**

1.922 inches

**External Key Quantity:**

13

**Material Thickness:**

Between 0.046 inches and 0.054 inches

**Material:**

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1035

**Surface Treatment:**

Cadmium and chromate or zinc and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification 1st treatment response or astm b633, type 2, class 3 assn standard 2nd treatment response

**Style Designator:**

Key

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A022b0