

View Online at <https://aerobasegroup.com/nsn/5310-00-208-4177>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Counterbore Diameter:**

0.383 inches nut and 0.388 inches nut

**Mounting Hole Diameter:**

Between 0.130 inches and 0.135 inches

**Nut Style:**

Plate

**Nut Length:**

Between 1.516 inches and 1.546 inches

**Nut Height:**

Between 0.751 inches and 0.781 inches

**Plate Thickness:**

Between 0.045 inches and 0.075 inches

**Plate Width:**

Between 0.923 inches and 0.953 inches

**Nut Counterbore Depth:**

0.292 inches nut and 0.302 inches nut

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.610 inches and 0.640 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 1.248 inches and 1.252 inches

**Thread Series:**

Unf

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Countersink Angle:**

100.0 degrees nut

**Material:**

Steel comp 1212 nut

**Material Specification:**

Ams 5010 assn standard single material response nut

**Surface Treatment:**

Cadmium nut

**Surface Treatment Specification:**

Qq-p-416, type 1 cl 3 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0