NSN 5310-00-209-0786

Lock Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-209-0786

Hole Diameter:

Between 0.256 inches and 0.267 inches

Outside Diameter:

Between 0.494 inches and 0.510 inches

Material Thickness:

Between 0.023 inches and 0.028 inches

End Application:

W/s: aircraft, (ac-130h, mc-130h, ec-130e, hc-130); compressor, reciprocating m4; airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a); aviation engine test systems (aets); support equipment, b-1 aircraft; central message switch, an/tyc-39a; boile; medium mine protected vehicle - mmpv

Hardness Rating:

Between 40.0 rockwell c and 50.0 rockwell c

Material:

Steel comp 1050 or steel comp 1551 or steel comp 1552 or steel comp 1053 or steel comp 1055 or steel comp 1059 or steel comp 1060 or steel comp 1561 or steel comp 1064

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Flat external teeth

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A022b0