NSN 5310-00-225-8309

Round Plain Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-225-8309

| Thread Pitch Diameters: |
|---|
| +0.5657/+0.5687 inches |
| Thread Direction: |
| Right-hand |
| Drive Point Depth: |
| 0.094 inches |
| Nut Style: |
| Round |
| Nut Diameter: |
| Between 0.980 inches and 1.010 inches |
| Nut Thickness: |
| Between 0.303 inches and 0.323 inches |
| Drive Point Width: |
| Between 0.120 inches and 0.130 inches |
| Drive Point Quantity: |
| 4 |
| Thread Series: |
| Uns |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| Between 66.0 rockwell b and 92.0 rockwell b |
| Thread Size: |
| 0.586 inches |
| Material: |
| Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 102 |
| or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp |
| 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 |
| Material Specification: |
| 66 federal standard all material responses |
| Surface Treatment: |
| Cadmium and chromate or zinc |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class c federal specification 1st treatment response or qq-z-325, type 2, class 3 federal specification 3rd treatment |
| response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A021a0 |