

View Online at <https://aerobasegroup.com/nsn/5310-00-226-5978>

Hole Diameter:

Between 0.801 inches and 0.816 inches

Outside Diameter:

Between 1.110 inches and 1.140 inches

Internal Prebent Key Length:

Between 0.062 inches and 0.093 inches

External Prebent Key Width:

Between 0.146 inches and 0.166 inches

Internal Prebent Key Width:

Between 0.156 inches and 0.176 inches

Overall Distance Including Keys:

1.531 inches

External Key Quantity:

11

Material Thickness:

Between 0.038 inches and 0.046 inches

Hardness Rating:

Between 50.0 rockwell b and 81.0 rockwell b

Material:

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1035 or steel comp 1023 or steel comp 1524 or steel comp 1025

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416 ty2 cl3 federal specification 1st treatment response or qq-z-325 ty2 cl3 federal specification 2nd treatment response

Style Designator:

Key

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0