AeroBase Group

View Online at https://aerobasegroup.com/nsn/5310-00-227-5259

| view Online at https://aerobasegroup.com |
|--|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Counterbore Diameter: |
| 0.254 inches nut |
| Lubrication: |
| Dry film lubricant |
| Overall Length: |
| 1.687 inches |
| Overall Width: |
| 0.516 inches |
| Nut Style: |
| Gang channel, self locking |
| Channel Style: |
| Straight type |
| Assemblyheight: |
| 0.281 inches |
| Channel Height: |
| 0.281 inches |
| Nut Spacing: |
| Between 0.865 inches and 0.885 inches |
| Nut Counterbore Depth: |
| 0.017 inches nut |
| Tempurature Rating: |
| 250.0 degrees fahrenheit |
| Nut Quantity: |
| 2 |
| Thread Series: |
| Unjf |
| Features Provided: |
| Floating nut |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.250 inches |
| Material: |
| Steel nut |
| Surface Treatment: |
| Cadmium nut |
| |

NSN 5310-00-227-5259 Gang Channel Self-locking Nut Assembly - Page 2 of 2



Surface Treatment Specification:

Qq-p-416 federal specification single treatment response nut

Specification Data:

80205-nas690 professional/industrial association standard

Departure From Cited Document:

As modified by revision 8

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.