

View Online at <https://aerobasegroup.com/nsn/5310-00-241-6638>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Nut Style:

Hexagon

Nut Height:

Between 0.298 inches and 0.328 inches

End Application:

Rg-33 auv mrap

Width Across Flats:

Between 0.553 inches and 0.564 inches

Tempurature Rating:

250.0 degrees fahrenheit

Thread Series:

Unc

Thready Qty Per Inch (tpi):

18

Thread Size:

0.312 inches

Countersink Angle:

88.0 degrees nut

Bearing Surface Type:

Chamfered

Bearing Surface Finish:

125.0 microinches

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp w214 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp m3 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 nut

Material Specification:

Mil-m-20693, comp a, type 1 military specification single material response locking insert

Surface Treatment:

Passivate nut

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-m-20693 spec.