

View Online at <https://aerobasegroup.com/nsn/5310-00-255-0010>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Nut Style:

Hexagon

Nut Height:

Between 1.578 inches and 1.640 inches

Width Across Flats:

Between 2.159 inches and 2.197 inches

Tempurature Rating:

250.0 degrees fahrenheit

Thread Series:

Unc

Thready Qty Per Inch (tpi):

6

Thread Size:

1.500 inches

Countersink Angle:

88.0 degrees nut

Bearing Surface Type:

Chamfered

Bearing Surface Finish:

125.0 microinches

Material:

Steel comp 301 nut or steel comp 302 nut or steel comp 302b nut or steel comp 303 nut or steel comp 303se nut or steel comp 304 nut or steel comp 304l nut or steel comp 305 nut or steel comp w214 nut or steel comp 309 nut or steel comp 309s nut or steel comp 310 nut or steel comp 310s nut or steel comp m3 nut or steel comp 316 nut or steel comp 316l nut or steel comp 317 nut or steel comp 321 nut or steel comp 347 nut or steel comp 348 nut or steel comp 384 nut or steel comp 385 nut

Material Specification:

Mil-m-20693, comp a, type 1 military specification single material response locking insert

Surface Treatment:

Passivate nut

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-m-20693 spec.