

View Online at <https://aerobasegroup.com/nsn/5310-00-262-6355>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Lubrication:**

Soluble lubricant

**Nut Style:**

Hexagon

**Nut Height:**

Between 0.229 inches and 0.249 inches

**End Application:**

Mrap - cougar cat1 a1; mrap - m-atv ui; mrap - cougar iss 1.0

**Width Across Flats:**

Between 0.367 inches and 0.376 inches

**Tempurature Rating:**

250.0 degrees fahrenheit

**Thread Series:**

Unc

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.190 inches

**Bearing Surface Type:**

Chamfered

**Bearing Surface Finish:**

125.0 microinches

**Material:**

Steel comp 303 or steel comp 303se or steel comp 303 plus x nut

**Material Specification:**

Ams 5640 assn standard all material responses nut

**Surface Treatment:**

Passivate except insert

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-m-20693 spec.