## NSN 5310-00-275-1396

Clinch Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-275-1396

| Thread Class:  |
|--|
| 3b   |
| Thread Direction:  |
| Right-hand   |
| Locking Feature:   |
| Prevailing torque all metal design                                     |
| Pilot Diameter:  |
| Between 0.220 inches and 0.224 inches                                  |
| Pilot Length:  |
| Between 0.058 inches and 0.068 inches                                  |
| Counterbore Diameter:  |
| 0.165 inches nut and 0.170 inches nut                                  |
| Lubrication:   |
| Soluble lubricant  |
| Nut Style:   |
| Clinch   |
| Nut Height:  |
| Between 0.218 inches and 0.248 inches                                  |
| Nut Counterbore Depth:   |
| 0.048 inches nut and 0.058 inches nut                                  |
| Width Across Flats:  |
| Between 0.305 inches and 0.313 inches                                  |
| Tempurature Rating:  |
| 450.0 degrees fahrenheit   |
| Thread Series:   |
| Unjc   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Thread Size:   |
| 0.138 inches   |
| Material:  |
| Steel  |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:                                       |
| Qq-p-416, type 1, cl 3 federal specification single treatment response |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
|  |

## NSN 5310-00-275-1396

Clinch Self-locking Nut - Page 2 of 2

Fiig: A021a0

