
# NSN 5310-00-283-7525

Plate Self-locking Nut - Page 1 of 2





# Thread Class:

3b

**Thread Direction:** 

**Right-hand** 

### Locking Feature:

Prevailing torque all metal design

## **Counterbore Diameter:**

0.254 inches nut

#### Mounting Hole Diameter:

0.098 mils and 0.103 centimeters

#### Nut Style:

Plate

#### Nut Length:

1.306 inches

#### Nut Height:

0.342 inches

### Plate Thickness:

0.032 inches

### Plate Width:

0.539 inches

#### Removable Nut Manufacturer Code:

72962

#### Nut Counterbore Depth:

0.125 inches nut

#### **Nut Mounting Provision:**

Straight holes

#### Mounting Hole Arrangement Style:

2 holes

#### Distance From Aperture Center To Mounting Hole Center:

Between 0.495 inches and 0.505 inches

#### Center To Center Distance Between Mounting Holes Along Length:

Between 0.310 inches and 0.314 inches

#### Removable Nut Manufacturer Part Number:

G19421-2-4

#### **Tempurature Rating:**

450.0 degrees fahrenheit

#### Thread Series:

Unjf

#### **Features Provided:**

Floating nut

#### Thready Qty Per Inch (tpi):

28

# NSN 5310-00-283-7525

Plate Self-locking Nut - Page 2 of 2



**Thread Size:** 

0.250 inches

Material:

Steel nut

Surface Treatment:

Cadmium shell

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response shell

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A021a0