NSN 5310-00-286-9642

Flat Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-286-9642

Rectangular Edge Shape: Round Center Hole Shape: Round willats Thickness: Between 0.245 inches and 0.255 inches Overall Diameter: Between 0.460 jinches and 4.841 inches Hole Wildth Across Flats: Between 3.877 inches and 3.82 inches Min. Tonsile Strength (ps): 150000 pounds per square inch Hardness Rating: Between 3.40 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure:	Cross Sectional Shape:
Round 'Illats Thickness: Between 0.245 inches and 0.255 inches Overall Diameter: Between 1.609 inches and 4.641 inches Hole Wildth Across Flats: Between 4.609 inches and 3.882 inches Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: Between 3.40 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Hoat Treatment: As fabricated Material Specification: Mill-se758, cond c military specification single material response Test Data Document: 81349-mil-18688 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheft Life: Via Unit Of Measure:	Rectangular
Center Hole Shape: Round wilflats Thickness: Between 0.245 inches and 0.255 inches Overall Diameter: Between 4.609 inches and 4.641 inches Hole Width Across Flats: Between 3.877 inches and 3.882 inches Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typicar", "average", ", etc.). Shelf Life: Na Unit Of Measure:	Edge Shape:
Round wilflats Thickness: Between 0.245 inches and 0.255 inches Overall Diameter: Between 4.609 inches and 4.641 inches Hole Width Across Flats: Between 3.877 inches and 3.882 inches Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average", "', etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A022b0 Mil-istd (millitary Standard):	Round
Thickness: Between 0.245 inches and 0.255 inches Overall Diameter: Between 4.609 inches and 4.641 inches Hole Width Across Flats: Between 3.877 inches and 3.882 inches Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: Between 3.4.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6808 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: Demilitarization: No Fig: A022b0 Mil-set (military Standard):	Center Hole Shape:
Between 0.245 inches and 0.255 inches Overall Diameter: Between 4.609 inches and 4.641 inches Hole Width Across Flats: Between 3.877 inches and 3.822 inches Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure: Demilitarization: No Filig: A022b0 Mil-std (military Standard):	Round w/flats
Overall Diameter: Between 4.609 inches and 4.641 inches Hole Width Across Flats: Between 3.877 inches and 3.882 inches Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-1-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Filig: A022b0 Mil-std (millitary Standard):	Thickness:
Between 4.609 inches and 4.641 inches Hole Width Across Flats: Between 3.877 inches and 3.882 inches Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: Between 3.4.0 rockwell c and 38.0 rockwell c Surface Flisih: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mills-6758, cond c military specification single material response Tost Data Document: 81349-mill-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: Demilitarization: No Flig: A022b0 Mil-std (military Standard):	Between 0.245 inches and 0.255 inches
Hole Width Across Flats: Between 3.877 inches and 3.882 inches Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: V/a Unit Of Measure: Demilitarization: No Filig: A02250 Mil-std (military Standard):	Overall Diameter:
Between 3.877 inches and 3.882 inches Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A022b0 Mil-std (military Standard):	Between 4.609 inches and 4.641 inches
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-6688 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Hole Width Across Flats:
150000 pounds per square inch Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A022b0 Mil-std (military Standard):	Between 3.877 inches and 3.882 inches
Hardness Rating: Between 34.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Min. Tensile Strength (psi):
Between 34.0 rockwell c and 38.0 rockwell c Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	150000 pounds per square inch
Surface Finish: 100.0 microinches all surfaces Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Hardness Rating:
Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Between 34.0 rockwell c and 38.0 rockwell c
Heat Treatment: As fabricated Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Surface Finish:
Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	100.0 microinches all surfaces
Material: Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Heat Treatment:
Steel Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	As fabricated
Material Specification: Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Material:
Mil-s-6758, cond c military specification single material response Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Steel
Test Data Document: 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Material Specification:
81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Mil-s-6758, cond c military specification single material response
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A022b0 Mil-std (military Standard):	N/a
No Fiig: A022b0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A022b0 Mil-std (military Standard):	
Fiig: A022b0 Mil-std (military Standard):	Demilitarization:
A022b0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A022b0
Mil-s-6758 spec.	Mil-std (military Standard):
	Mil-s-6758 spec.