NSN 5310-00-324-7280

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-324-7280 **Thread Class:** 2b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with metallic insert **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** Between 0.975 inches and 0.995 inches **Nut Height:** Between 2.380 inches and 2.420 inches **Plate Thickness:** Between 0.050 inches and 0.070 inches Plate Width: Between 0.386 inches and 0.406 inches **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** 0.344 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.686 inches and 0.690 inches **Thread Series:** Unf Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches Material: Stainless steel locking insert **Material Specification:** Mil-a-12545, t6 military specification single material response nut **Surface Treatment:** Passivate locking insert **Surface Treatment Specification:**

Mil-a-8625, type 1 military specification 1st treatment response nut or mil-c-5541 military specification 2nd treatment response nut

Shelf Life:

N/a

NSN 5310-00-324-7280

Plate Self-locking Nut - Page 2 of 2



	nit	O+	Measure:
u		v	wicasuic.

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-12545 spec.