
NSN 5310-00-339-8137

Plate Self-locking Nut - Page 1 of 2





| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Lubrication: |
| Dry film lubricant |
| Mounting Hole Diameter: |
| Between 0.130 inches and 0.135 inches |
| Nut Style: |
| Plate |
| Nut Length: |
| 1.292 inches |
| Nut Height: |
| 0.344 inches |
| Plate Thickness: |
| 0.055 inches |
| Plate Width: |
| 0.614 inches |
| Nut Mounting Provision: |
| Straight holes |
| Mounting Hole Arrangement Style: |
| 2 holes |
| Distance From Aperture Center To Mounting Hole Center: |
| Between 0.495 inches and 0.505 inches |
| Center To Center Distance Between Mounting Holes Along Length: |
| Between 0.998 inches and 1.002 inches |
| Tempurature Rating: |
| 450.0 degrees fahrenheit |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.375 inches |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2 federal specification single treatment response |
| |
| |
| |

NSN 5310-00-339-8137

Plate Self-locking Nut - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

