## NSN 5310-00-376-8728



Gang Channel Self-locking Nut Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5310-00-376-8728

| Thread Class:  |
|--|
| 3b   |
| Thread Direction:  |
| Right-hand   |
| Locking Feature:   |
| Prevailing torque all metal design   |
| Counterbore Diameter:  |
| 0.194 inches nut   |
| Lubrication:   |
| Dry film lubricant   |
| Overall Length:  |
| 72.000 inches  |
| Overall Width:   |
| 0.433 inches   |
| Nut Style:   |
| Gang channel, self locking   |
| Channel Style:   |
| Straight type  |
| Assemblyheight:  |
| 0.312 inches   |
| Channel Height:  |
| 0.203 inches   |
| Nut Spacing:   |
| 0.875 inches   |
| Nut Counterbore Depth:   |
| 0.125 inches nut   |
| Tempurature Rating:  |
| 350.0 degrees fahrenheit   |
| Nut Quantity:  |
| 82   |
| Thread Series:   |
| Unf  |
| Features Provided:   |
| Floating nut   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Thread Size:   |
| 0.190 inches   |
| Material:  |
| Iron alloy 660 nut   |
| Material Specification:  |
| Ams 5525 assn standard 2nd material response nut or ams 5735 assn standard 2nd material response nut |

## NSN 5310-00-376-8728

Mil-std (military Standard):

Mil-a-8625 spec.

Gang Channel Self-locking Nut Assembly - Page 2 of 2



| Surface Treatment:  |
|---|
| Anodize channel   |
| Surface Treatment Specification:                                    |
| Mil-a-8625 military specification single treatment response channel |
| Specification Data:   |
| 76301-st3-473 manufacturers standard                                |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A021a0  |