NSN 5310-00-402-5711

Assembled Washer Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-402-5711 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Washer Outside Diameter:** Between 0.460 inches and 0.490 inches **Counterbore Diameter:** 0.230 inches nut and 0.240 inches nut **Overall Height:** Between 0.334 inches and 0.374 inches **Nut Style:** Flat with turned back edge **Nut Counterbore Depth:** 0.141 inches nut and 0.161 inches nut Width Across Flats: Between 0.367 inches and 0.376 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unjf Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Bearing Surface Finish:** 125.0 microinches Material: Steel comp 1137 nut or steel comp 11137 nut or steel comp 8740 nut **Material Specification:** Qq-a-225/6, t4 federal specification 1st material response washer or qq-a-250/13, t6 federal specification 2nd material response washer **Surface Treatment:** Cadmium nut and chromate nut **Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response nut Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5310-00-402-5711

Assembled Washer Self-locking Nut - Page 2 of 2



Fiig:

A021a0

Mil-std (military Standard):

Mil-c-5541 spec.